

Product features

United is a shear-bolt coupling system for the connection of concrete reinforcement bars from Ø12 to 50 mm (ASTM #4 to #18).

Bar size		Order	Coupler dimensions (mm)			Total number
Metric	UK	codes	Outside diameter (D)	Length (L)	Screw size	of screws
12, 12.5	12	FPUS0400002	48	140	M12	6
14, 16	16	FPUS0500002	48	140	M12	6
18, 20	-	FPUS0600002	52	200	M12	8
-	20	FPUS0700002	59	180	M16	6
22	-	FPUS0700003	59	240	M16	8
24, 25, 26	25	FPUS0800002	62	240	M16	8
28	-	FPUS0900002	76	220	M20	6
30, 32	32	FPUS1000002	83	280	M20	8
34, 36	-	FPUS1100002	89	360	M20	10
38, 40	40	FPUS1200002	95	425	M20	12
50	-	FPUS5000002	107	620	M20	18

Transition splicing between two different rebar diameters is also possible using the following models:

Larger bar size		Smaller bar size		Order	
Europe	UK	Europe	UK	codes	
24, 25, 26	25	22	-	FPUS0800002	
30, 32	32	24, 25, 26	25	FPUS1000002	
		28		11 031000002	

Product features Benefits Packing & Applications Quality & Approvals References

Benefits

- Site assembly with standard impact wrench.
- No need of bar end preparation.
- Readily available off the shelf.
- Ideal for concrete-embedded bars, repair and retrofit works, bent bars, etc.
- Type 2 splice as per ACI 318 requirements.
- Complies with BS 8110 and NF A35-020 standards.



Product features | Benefits | Packing & Applications | Quality & Approvals | References

4 Dextra | UNTEC | The Universal Splicing System

Packing


Unitec couplers are packed in wooden crates that should be stored under a roof and protected from natural elements.

Bar size		Order	Qty / box	Net weight	Gross
Metric	UK	codes	(pieces)	(kg)	weight (kg)
12, 12.5	12	FPUS0400002	200	268	292
14, 16	16	FPUS0500002	200	254	280
18, 20	-	FPUS0600002	100	199	224
-	20	FPUS0700002	100	239	264
22	-	FPUS0700003	50	152	177
24, 25, 26	25	FPUS0800002	50	169	194
28	-	FPUS0900002	50	284	308
30, 32	32	FPUS1000002	50	393	418
34, 36	-	FPUS1100002	20	225	250
38, 40	40	FPUS1200002	10	143	168
50	-	FPUS5000002	10	236	261

Note: The weight of the crates varies depending on ambient humidity

Please ensure that order quantities are a multiple of the packaging quantities stated in the table. External dimensions of crate = W 83.4 cm, L 63.4 cm, H 29.0cm.

Applications



Remote locations

Repair and retrofitting

Product features Benefits Packing & Applications Quality & Approvals References

5 Dextra | **UNPTEC** | The Universal Splicing System

Quality assurance







Dextra's Quality Management System complies with the requirements of:

- Bureau Veritas ISO 9001:2015 TH010882
- UK CARES ISO 9001:2015 1086
- ASME QSC-706

Each coupler is marked with symbols that enable to trace back to each raw material and production batch data.

Approvals & Certifications

Unitec couplers have been certified by the following authorities:





- ASTM A615 grade 60, 75 and 80
- ASTM A705 grade 60 and 80
- ISO 6935-2 grade B500B












AFCAB for use with grade B500B and bars Ø 12 to 40mm as per NF A35080.



• Dubai Municipality Approval for bars Ø 12 to 40mm grade 500.








• Australian Technical Approval for bars Ø 20 to 36mm as per A5660406.



DIBt for use with grade B500B and bars Ø 12 to 28mm as per DIN 488-1.

Product features Benefits Packing & Applications Quality & Approvals References



Project References



Resources







Brochure Assembly instruction





Connect with us









Product features Benefits Packing & Applications Quality & Approvals

References





Dextra

www.dextragroup.com/contact

Dextra Building Products (Guangdong) Co., Ltd. Tel: (86) 20 2261 9901

HONG KONG Dextra Pacific Ltd. Tel: (852) 2511 8236

HEADQUARTERS THAILAND

Tel: (66) 2 021 3800

Dextra Manufacturing Co., Ltd.

EUROPE Dextra Europe SARL. Tel: (33) 1 45 53 70 82

MIDDLE EAST Dextra Middle-East FZE Tel: (971) 4886 5620

INDIA Dextra India Pvt. Ltd. Tel: (91) 22 2839 2694 **NORTH AMERICA** Dextra America Inc. Tel: (1) 206 742 6020

LATIN AMERICA Dextra Latam Tel: (507) 831 1442

Product features Benefits Packing & Applications Quality & Approvals References